

Product datasheet

Specifications



Battery Breaker Box, two 630A DC breakers, for Galaxy VS/VL, Easy UPS 3-Phase Modular, and Easy UPS 3M Advanced

GVBBB630EL-2CB

Overview

Presentation	Wall mounted battery breaker box for use with third party battery solutions.
Lead Time	Usually Ships within 2 Weeks

Main

Product Or Component Type	Box
Battery Type	VRLA Li-Ion (Lithium-Ion)

Physical

Colour	White
Height	100 cm
Width	75 cm
Depth	28 cm
Net Weight	66 kg

Conformance

Standards	IEC 62040-1-2 IEC 60721-4-2 level 2M2
Product Certifications	CE RCM EAC

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature For Storage	-25...55 °C
Storage Relative Humidity	0...95 % non-condensing

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	594 mm
Package 1 Width	1200 mm
Package 1 Length	1000 mm

Package 1 Weight

76 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

 **Rohs Exemption Information** Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)