

Uniflair InRow RC, 300mm, Chilled Water, 100-240V, 50/60 Hz - ST

ACRC301S

Overview

Lead Time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	100120 V 200240 V
Input Connection Type	IEC 60309 16 A 2P + E NEMA L5-20P
Number Of Rack Unit	42U
Number Of Cables	2
Provided Equipment	Installation guide

General

Air Discharge Option	Horizontal
Intake Air Option	Rear return
Air Flow	1510.23 l/s
Minimum Water Inlet Temperature	7 °C
Condensate Pump Flow	0.00 m3/h

Physical

Colour	Black
Height	199.1 cm
Width	30 cm
Depth	109.5 cm
Net Weight	184 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

Number Of Feeders	2
Input Power	800 W
Network Frequency	50/60 Hz

Conformance

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Product Certifications	C-Tick	
	CE	
	GOST	
	MEA	
	VDE	
Standards	EN 55022 class A	
	EN 55024	
	EN 60950	
	IEC 60950	
	IEC 61000-3-2	
	IEC 61000-3-3	

Communications & Management

Control Panel Multifunction LCD status and control console

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	211.8 cm
Package 1 Width	113.7 cm
Package 1 Length	74.6 cm
Package 1 Weight	192 kg

Contractual warranty

Warranty 1 year (parts only)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Under investigation